

● 开关基本参数

机械寿命	1,000,000 cycles min.
接触电阻	50mΩ max. initial
绝缘电阻	100 MΩ min.
抗电强度	1500VAC for 55 +/- 5 sec
外壳材料	UL 94V-0 Thermoplastic
	IEC 60335-1 Ed 4 Compliant



型号	使用温度	额定负载	电寿命(UL)	电寿命(EN)	电寿命(CQC)
V52	40T125	16(4)A 125/250VAC		50,000 cycles	50,000 cycles
		16A, 125/250V	6,000 cycles		
		1/2HP 125V	6,000 cycles		
		3/4HP, 250V	6,000 cycles		
		0.4 A, 125 V DC	6,000 cycles		
		0.2 A, 250 V DC	6,000 cycles		
		10.1A, 125VL	6,000 cycles +6,000 cycles		
V53	40T85	22A 125/250VAC	6,000 cycles	-	-
		1HP 125VAC; 2HP 250VAC	6,000 cycles	-	-
		15.1A 125/250VAC	6,000 cycles	-	-
		12A, 125VL	6,000 cycles +6,000 cycles	-	-

● 开关选型

	V51	A	M	-	A	A	00	AG	-	01
产品类型										
V52										
电路										
A= SPDT B= SPST-NC C= SPST-NO										
操作力										
K, L, M, N, P (Ref. to E4-7)										
端子类型										
A, B, C ... (Ref. to E4-7)										
杠杆位置										
A= Standard Position N= Pin Plunger, No External Lever B= High Gear Position										
杠杆类型										
01, 02, 03 ... 00 = No Lever (Ref. to E4-7)										
触点类型										
AG = Serrated Silver Contact										
版本										
01 = Standard										

